

The Movotec® Dual Drive "Bolt-On" Lift Systems can be supplied with 6 or 8 cylinders and can lift up to 1134 kg. / 2500 lbs.

System Includes

- Two synchronized Motor Driven Systems with controller and switch
- 6 cylinder "Bolt-On" lift systems use one 2.5m (8ft.) and two 3m (10ft.) sections of flexible tubing per pump
- 8 cylinder "Bolt-On" lift systems use two 2.5m (8ft.) and two 3m (10ft.) sections of flexible tubing per pump
- Glides for each lift cylinder
- Drilling templates, tubing clips and cable ties
- Installation and operating instructions

Movotec® Dual Drive Lift Systems are shipped assembled and ready for installation.



Optional:
Motor Cover 662-00039



Lift System Dimensions

# of Cylinders	System Lift Capacity (kg / lbs.)	Adjustment Range* (mm / in.)	Motor-Driven System (120V) Part Number	Motor-Driven System (230V)** Part Number	Includes Pump (x2)	Includes Cylinders (x6)
6	680 / 1500	150 / 5.9	MLS-00020	MLS-00028	Q3612	CB415
	680 / 1500	200 / 7.9	MLS-00021	MLS-00029	Q3615	CB420
	680 / 1500	300 / 11.8	MLS-00022	MLS-00030	Q3623	CB431
	680 / 1500	400 / 15.7	MLS-00023	MLS-00031	Q3631	CB440
8	907 / 2000	150 / 5.9	MLS-00024	MLS-00032	Q4612	CB415
	907 / 2000	200 / 7.9	MLS-00025	MLS-00033	Q4615	CB420
	907 / 2000	300 / 11.8	MLS-00026	MLS-00034	Q4623	CB431
	907 / 2000	400 / 15.7	MLS-00027	MLS-00035	Q4631	CB440
	1134 / 2500	150 / 5.9	MLS-00090	MLS-00094	Q4615	CB615
	1134 / 2500	230 / 9.1	MLS-00091	MLS-00095	Q4623	CB631
	1134 / 2500	300 / 11.8	MLS-00092	MLS-00085	Q4631	CB631
	1134 / 2500	400 / 15.7	MLS-00093	MLS-00097	Q4639	CB640

* The adjustment range is reduced for motorized systems by 6-8mm

** 230V System supplied with Schuko plugs

Note: 5 and 7 cylinder systems provided on request. Larger load capacity available upon request